



RING BRACKET

HOUSING

RING LOCK

COVER

Top view

1/4" NPT INLET
4 PLACES

Ø11.75" [Ø298.499]

Ø9.00" [Ø228.600]

Front view

| | | | | | | | | | | | |
|------------------------|----------|---|----------------|--|---|--|--|--|---|--|---|
| THIRD ANGLE PROJECTION | | <p>REQUIREMENTS—UNLESS OTHERWISE SPECIFIED</p> <p>GENERAL</p> <p>1. DIMS ARE IN INCHES (MM)</p> <p>2. DIMENSIONING AND TOLERANCING IN ACCORDANCE WITH ANSI Y14.5 (1982)</p> <p>3. MACHINE FINISH 125 MICRO INCH RMS</p> <p>4. INTERNAL RADI .015</p> <p>5. BREAK SHARP CORNERS .005 TO .015</p> | | | | <p>CONTRACT NUMBER —</p> <p>CLIENT —</p> <p>CONTRACTOR —</p> | | <p>NEX FLOW AIR PRODUCTS CORP. 10520 YONGE STREET, UNIT 35B-220, RICHMOND HILL, ON L4C 3C7 TEL.: (416) 410-1313 & FAX: (416) 410-1806 www.nex-flow.com</p> | | | |
| | | <p>LIMITS</p> <p>1. LINEAR DIMS. .XXX = .005 .XX = .010 .X = .030 " = ± 1/2"</p> <p>2. ANGLES = ± 1/2"</p> <p>3. RUNOUT .010 TIR</p> <p>4. HOLES IN ACCORDANCE WITH AND 10387</p> | | | | <p>DRAWN CHIRAG.S</p> <p>DATE 22/02/2016</p> <p>DESIGN CHECKED</p> | <p>PROJECT —</p> <p>STRESS —</p> <p>THERMAL —</p> <p>MECHANISM —</p> | <p>MANUFACTURING —</p> <p>MATERIALS —</p> <p>ELECTRICAL —</p> | <p>MACHINE NAME :—</p> <p>9" RING BLADE</p> | | <p>PART NAME :—</p> <p>OUTLINE</p> |
| MATERIAL | AL/SS304 | <p>NEXT ASSEMBLY</p> <p>USED ON</p> <p>QTY PER ASSY</p> <p>PART NO</p> | <p>PART NO</p> | <p>CONTRACT NUMBER</p> <p>CLIENT</p> <p>CONTRACTOR</p> | <p>DRAWN</p> <p>DATE</p> <p>DESIGN</p> <p>CHECKED</p> | <p>PROJECT</p> <p>STRESS</p> <p>THERMAL</p> <p>MECHANISM</p> | <p>MANUFACTURING</p> <p>MATERIALS</p> <p>ELECTRICAL</p> | <p>MACHINE NAME</p> <p>9" RING BLADE</p> | <p>PART NAME</p> <p>OUTLINE</p> | <p>SIZE</p> <p>CAGE CODE</p> <p>DWG NO</p> <p>RELEASE</p> <p>REV</p> | <p>SCALE</p> <p>1:1</p> <p>CAD NO</p> <p>SHEET 1 OF 1</p> |